

SUPER CHARGE YOUR PRODUCTION

Bandit chippers are easier to feed, so you'll be more productive during the day. Bandit's unique Slide Box feed system and powerful dual horizontal feed rollers, which are 20" wide by 10.625" in diameter and powered by a pair of 32.3 CID hydraulic motors, crush and compress material, easily guiding it to the drum.

PACK TRAILERS FULLER

Bandit is known throughout the industry for packing trailers fuller, reducing the number of trips to the dump site. Bandit chippers feature smooth discharge transitions eliminate restrictions and deep knife pockets propel chips with tremendous force.

MAXIMIZE YOUR UPTIME


The most common maintenance items are easy to access on Bandit chippers. Bolt-in knives are easy to access and change through the chipper hood. And all service areas are easy to access, including all grease points, so daily maintenance is simple and quick.

RUGGED CONSTRUCTION

Heavy-duty components help ensure long life and trouble-free operation, even when chipping tough materials. The chipper disc, housing and shaft are so rugged that very rarely do they need to be replaced.



6750 Millbrook Rd. • Remus, MI 49340 • **1-800-952-0178**



Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments

SPECIFICATIONS

MEASUREMENTS	TOWABLE		HD	
Length:	18' 8"	569 cm	21'	640.1 cm
Width:	7' 4"	223.5 cm	7' 4"	223.5 cm
Height:	9' 6"	289.6 cm	9' 6"	289.6 cm
Weight:	9,500 - 10,500 lbs. (4,309 - 4,762.7 kg)		12,500 lbs. (5,669.9 kg)	
Engines:	139-174 HP (104-130kW)		200-225 HP (149-168kW)	
Fuel Tank:	30 gal.	113.6 L	60 gal.	227.1 L
Hydraulic Tank:	32 gal.	121.1 L	32 gal.	121.1 L

DERO		

Towable/HD: (1) 12,000 pound (5,443 kg) air brake axles with (2) 235/75R 17.5" (44.5 cm) tires mounted on polished aluminum rims

Standard & Custom Colors Available

Choose from six standard colors, or select a custom color to match your fleet.











White

DIMENSIONS					
Capacity:	18" Capacity	45.7 cm Capacity			
Opening:	18" x 20.5" wide	45.7 cm x 52.1 cm wide			
Disc:	55" dia. x 2" thick	140 cm dia. x 5.1 cm thick			
RPM:	Approximately 850 RPM				
Hitch: 2 position, 2.5" (6.35 cm) pintle hitch					
Discharge: Standard with 3 position manual crank swivel					
Feed System: Slide box feed system with (2) 21" (53.3 cm) adjustable springs					

Frame: All of our frames are made from 12" (30.5 cm) structural C-Channel with a web thickness of ½" (1.27 cm). This will apply to both track and trailer models.

The Bandit Backbone™ Support

The Bandit Backbone is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit hand-fed chipper -regardless the age, hours, or warranty status - the Bandit Backbone is here to support you.

We Are Here to Support You

There are nearly 200 dealer locations in the US and 61 international dealers to support you. They are factory trained. Plus we have an experienced parts and service department supporting you and our dealers.

- Last Chance Cables (standard) Stops/reverses the feed wheel when pulled in case of an emergency
- **Operator Safety Control Bar (standard)** Wraps around 3 sides of the infeed chute & controls the direction of feed wheels
- Wood Pusher Paddle (standard) Used to feed small wood debris into the chipper
- **Chipper Hood Pin w/Padlock (standard)** Prevents unauthorized access to the disc or drum
- Chipper Hood Engine Disable Plug (standard) Prevents engine from being started without the hood pin in place
- **Hydraulic Bottom Bump Bar (option)** Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels

Bandit Offers a Complete Line of Tree Care Equipment: Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments