

STUMP GRINDERS

Hydrostatic Stump Grinder

The Model 2550 is a high production stump grinder packed with power to meet the needs of professional stump grinding contractors who need a dependable and reliable workhorse. The Model 2550 features a heavy-duty atic motor to directly power the cutter wheel eliminating the need for a clutch, jackshaft, drive belt, belt tensioning system, and the many sheaves and bearings associated with those components. This substantially reduces downtime, increasing production while lowering operating costs. With gasoline and diesel Kubota engine options from 35 to 49 horsepower, the Model 2550 packs the punch to power through large jobs.

MANEUVERABLE AND POWERFUL

- · Low-maintenance hydrostatic dri
- Standard swing out manual control pane
- Available with 4WD, side-mounted manual controls, wireless remote control and grading blade







BANDIT INDUSTRIES

(DX(I)



With no drive belts, sheaves, bearings or clutches to worry about, engaging the cutter wheel is as simple as pushing a lever. Easy-to-use machine-mounted controls are intuitive and positioned to provide good visibility while grinding, allowing the operator to take full advantage of the 2550's capabilities. This reliable system delivers power directly to the cutter wheel with virtually no parasitic power loss.

High Power With Low Maintenance

Bandit's hydrostatic direct-drive stump grinders deliver all the stump grinding power demanded by professionals, without all of the maintenance normally associated with stump grinders. It's not uncommon for companies to see maintenance costs drop by as much as 30%, compared to traditional stump grinders.

Class-Leading Performance

The Model 2550 features a class-leading 53-1/2" cutter swing for grinding, while also grinding to a depth of 15". Equipped with the Bandit Revolution wheel as standard equipment, you'll spend less time repositioning and changing teeth and more time grinding.

Specifications

Dimensions:

LENGTH (W/BLADE): 120-1/2" HEIGHT: 72" Swing out Model 56" Kubota Remote or no swing out option WIDTH: 35.5" single wheels 51.5" dual wheels WFIGHT: 2,280 lbs. FUEL TANK: 8.5 gallons HYDRAULIC TANK: 8.5 gallons

Engine options:

GAS: 35-49.6 HP Kubota DIESEL: 49-49.6 HP

Cutter Wheel System:

CUTTER DEPTH: 15" **CUTTER HEIGHT:** 23-1/2" **CUTTER SWING:** 53-1/2"

WHEEL STYLE: Revolution WHEEL DIAMETER: 21" WHEEL THICKNESS: 1-1/4"

Drive System:

Self-propelled drive system with a travel speed of 140 FPM





pecifications, dimensions and options are subject to change without notice, and were current at the time of printing. Dimensions may vary, depending on option cted. Bandit Industries, Inc. reserves the right to change designs, specifications and options without prior notice. © 2015 Bandit Industries, Inc. All Rights Reser