STUMP GRINDERS



Pivoting Cutterwheel

The unique pivot-action base provides a sturdy platform for grinding while the operator swings the cutterhead from side to side. The weight is distributed and well-balanced so that the wheels are not likely to creep or rotate, allowing the operator to direct more of his energy into the pivoting cutterhead action rather than stabilizing the unit as a whole. This can seriously reduce operator fatigue in managing this durable unit's 700 lbs of weight and power.

Belt-Driven Power

The 15-1/4" diameter cutterwheel is driven by a belt directly from the motor. Engaging the unit is as simple as disengaging the clutch. Easy-to-use controls are intuitive and positioned to provide good visibility while grinding. This reliable system delivers power directly to the cutter wheel with virtually no parasitic power loss.

Class-Leading Performance

With a 30-1/2" width and self-propelled wheels, the HB-20 will easily go where other stump grinders can't.

Narrower Version Available

The Model HB-20 narrow version is 25" wide, allowing it to navigate tight passages with ease.

Specifications Standard Dimensions:

Self-Propelled:

LENGTH: 90" (handle down) 65.5" (handle up) **HEIGHT:** 47-1/2" (handle down) 65" (handle up)

WEIGHT: 700 lbs. 4.4 gallons **FUEL TANK:**

HYDRAULIC TANK: 2 gallons **CUTTER HEIGHT: CUTTER DEPTH: CUTTER WHEEL:**

DRIVE SYSTEM ENGINE OPTIONS: 15-1/4" diameter x 3/8" Greenteeth Wheel Self-Propelled 25 HP

22"

22"



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178 FIND US ONLINE | WWW.BANDITCHIPPERS.COM